



**McIntyre**

The gold standard in recycling systems

**5025BF**

**Metal Baler**



## McIntyre 5025BF Baler

Designed to act as both a baler and heavy duty yard shear, combining two pieces of machinery into one robust unit.

### Built to last

The combined features of the McIntyre 5025 BF (Bigfoot) allow the operator to both shear and bale material on one piece of equipment. Oversized sheets and extrusions can be handled with ease, reducing the amount of labour and machinery required - and in many cases eliminating the need for expensive cutting equipment. In line with all McIntyre equipment, this baler was originally designed for our own scrap yard use and is built to last.



### Why is this the best for you?

- cutting blades on 3 sides of the lid
- massive shear force
- low cost, reliable and effective
- a wide variety of applications
- quick cycle time

### About McIntyre Recycling Systems & Services


McIntyre is the gold standard in recycling systems and services, with 27,000 machines installed worldwide and a reputation for the widest and best-performing range of solutions for metal, waste, cars and aluminium. With scrap metal roots extending back to 1872, we have an unrivalled understanding of the challenges faced by scrap merchants, waste managers, car breakers, manufacturers, foundry managers and others with recycling responsibilities. As a result, the McIntyre name has become synonymous with innovative, problem-solving designs, robust products that deliver the best return on investment, and a knowledgeable, friendly and helpful service.

## Technical Data

<b>Machine dimensions:</b>	4090 x 1550mm x 1950mm 161" x 61" x 76"
<b>Chamber opening:</b>	1016mm x 507mm (40" x 20") L x W
<b>Loading height:</b>	860mm / (40")
<b>Bale Size:</b>	507mm x 254mm x Variable (20" x 10") x variable
<b>Weight with oil:</b>	5660kg
<b>Oil capacity:</b>	700 Litres / 55 Gallon
<b>Noise Level:</b>	78 +/- 3dBa
<b>Control:</b>	Manual Control
<b>Standard Electrical Requirements:</b>	2 x 11kW (2 x 15hp)
<b>Power Rating:</b>	63A / 3ph / 380-415v / 50Hz
<b>Motor speed:</b>	Approx. 960 rpm
<b>Max system Pressure:</b>	2250 psi / 155 Bar
<b>Max Compression Force:</b>	80 Tonnes
<b>Max Lid Shear Force:</b>	123 Tonnes

*While we make every effort to ensure that our information is correct, technical data is for guidance only and subject to change. If any dimension or performance indication is important to you, please check with us before ordering.*

© 2014 Copyright JMC Recycling Systems Ltd.  
All rights reserved



Postfach 55, CH-3700 Spiez  
Telefon (0041)33 437 47 44  
Fax (0041)33 437 70 73  
iut@iutbeyeler.com  
www.iutbeyeler.com  
Mitglied  BDSV

# IUT Beyeler AG

Ing. Unternehmen für Umwelt und Technik